

Three speed versatility and power reduces drying time by up to 50%!

FEATURES

- Selection of 3 speeds of air movement for maximum performance on every type of job.
- Rugged continuous duty motor with capacitor start, thermally protected with four-point mount.
- Rotationally molded polyethylene housing with molded offset handle and cord wrap.
- Three standing positions allow air to be directed at different angles.
- Maximum air movement of 3,000 cfm for rapid drying of carpet and hard floors.
- Built-in carpet clamp makes it easy to dry floors under carpets.
- 25' (7.6 meter) 16/3 SJTW cord with 3-wire molded plug
- Non-skid, non-marking rubber feet
- 1/2 HP, 110v or 220v/240v motor



Position Air Flow To Be Directed Where You Need It.



Flat – for carpets and
hard surfaces



90° - for ceilings and
ventilation

SPECIFICATIONS

ELECTRICAL:	120 volt, 60Hz
FAN WHEEL:	9.6" dia x 9.1" wide
FAN SPEEDS:	High – 1600 rpm Medium – 1350 rpm Low – 1050 rpm
AIRFLOW:	High – 3000 cfm Medium – 2500 cfm Low – 2000 cfm
POWER CABLE:	25 ft
WEIGHT:	33.5 Lbs. (15 Kg.)
DIMENSIONS:	20" (51 cm) L x 16" (41 cm) W x 18.8" (48 cm) H