

# MSDS Material Safety Data Sheet

Century 400

## Liquid Defoamer

MSDS Number: C125

Revision Date: March 27, 2006

Page 1 of 4

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer

Professional Chemicals Corporation  
325 S Price Rd 325 S. Price Rd.

Chandler Chandler, AZ AZ 85224 85224

Contact: EHS Manager EHS Manager

Telephone Number: 480-899-7000

FAX Number: 480-707-5661

E-Mail: [jphilips@prochem.com](mailto:jphilips@prochem.com)

Web [www.prochem.com](http://www.prochem.com)

Product Name: Liquid Defoamer

Revision Date: March 27, 2006

MSDS Number: C125

Emergency Telephone: (800) 535-5053 [Infotrac]

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

This product contains no hazardous components <1% nor any carcinogens <0.1%

#### OSHA Regulatory Status:

This MSDS Contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

### 3 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Skin; Inhalation; Ingestion;

Target Organs: Eyes; Skin;

Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material

Skin Contact: May Cause Irritation.

Eye Contact: May Cause Irritation.

Ingestion: Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause temporary injury.

HMIS III-ratings (scale 0-4): Health = 1, Fire = 0, Physical Hazard = 0

### 4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact: Promptly flush skin with water until all chemical is removed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation.

Ingestion: If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

# MSDS Material Safety Data Sheet

**Century 400**

## Liquid Defoamer

MSDS Number: C125

Revision Date: March 27, 2006

Page 2 of 4

### 5 FIRE FIGHTING MEASURES

**Flash Point:** >212°F  
**Flash Point Method:** Closed Cup

Use any standard agent - choose the one most appropriate for type of surrounding fire.

### 6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbant material and place into separate waste container. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

### 7 HANDLING AND STORAGE

**Handling Precautions:** Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor ( slippage). Keep away from sources of ignition. Wash thoroughly after handling.

**Storage Requirements:** Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or alkaline product.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Normal room ventilation is satisfactory for limited use.

**Protective Equipment:** HMIS PP, B | Goggles, Gloves

### 9 PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** White Opaque

**Physical State:** Liquid

**Odor:** Ammonia scent

**pH:** 6.5 - 7.5

**Vapor Pressure:** N/D

**Vapor Density:** N/D

**Boiling Point:** N/D

**Freezing/Melting Pt.:** N/D

**Solubility:** Soluble

**Spec Grav./Density:** 8.33 lb/gal

# MSDS Material Safety Data Sheet

Century 400

## Liquid Defoamer

MSDS Number: C125

Revision Date: March 27, 2006

Page 3 of 4

### 10 STABILITY AND REACTIVITY

<b>Stability:</b>	Product is stable under normal conditions.
<b>Conditions to avoid:</b>	None Known
<b>Materials to avoid (incompatibility):</b>	Strong oxidizing or alkaline agents
<b>Hazardous Decomposition products:</b>	Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
<b>Hazardous Polymerization:</b>	Will not occur.

### 11 TOXICOLOGICAL INFORMATION

Route of Entry: Eye contact, and Skin absorption/contact

Effects of Acute Overexposure to Product:

Eye Contact: Causes eye irritation, redness, tearing and blurred vision

Skin Contact: May cause skin irritation and defatting

Inhalation: Inhalation of mist or vapor may cause temporary respiratory irritation; temporary central nervous system effects including dizziness, weakness, fatigue, nausea, and headache.

Ingestion: May cause gastrointestinal temporary irritation with nausea, vomiting and diarrhea.

Effects of Chronic Overexposure to Product:

Exposure limits: N/D for mixture

Teratogenicity: None

Reproductive toxicity: None

Sensitization to Product: None known

Mutagenicity: None

Carcinogenicity: None

### 12 ECOLOGICAL INFORMATION

Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

### 13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

### 14 TRANSPORT INFORMATION

Not hazardous product according to DOT transport classifications.

### 15 REGULATORY INFORMATION

All ingredients for this product are listed on the TSCA inventory.

SARA Title III chemicals: None

California Prop 65 chemicals: None

CERCLA reportable quantity: None

RCRA hazardous waste no: None

# MSDS Material Safety Data Sheet

**Century 400**

---

## Liquid Defoamer

MSDS Number: C125

Revision Date: March 27, 2006

Page 4 of 4

**16**

### OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000

---

**END OF MSDS DOCUMENT**